

FEATURES



- Proprietary durable phosphor coating, for uniform solid appearance
- Multi-function PWM drivers, fully waterproof, featuring low power, high power, and turn signal modes
- Extremely bright, high-density LEDs that are visible even in direct sunlight
- Integrated mounting tabs for easy installation

GENERAL SPECIFICATIONS

| Product Function | Voltage Range | Current Draw* | Wattage | CCT/ Wavelength** | Lumen Output |
|------------------|---------------|---------------|---------|----------------------|--------------|
| Low | 9-16V | 120 mA | 1.6W | 620 nm | 40 lm |
| High | 9-16V | 450 mA | 5.9W | 620 nm | 155 lm |
| Turn | 9-16V | 910 mA | 12W | 620 nm | 290 lm |

*Current Draw @13.2v ***+/-500 Tolerance

Functions: Low Red, High Red, and Turn Signal Red outputs

Driver Type: Type G High Priority Driver

Connector Type: 2 Pin JST and 4 Pin JST with T-Tap

LED Type/Count: 3014 Red LED/ 150 Total

Operating Temperature: -40°C to 85°C

Length: 9" **Width:** 5.75" **Height:** 2.25"

Weight: 1lbs



What's Included:

- Two (2) LED halo rings
- Two (2) waterproof drivers
- Two (2) input wire pigtailed
- Eight (8) T-tap connectors
- Installation guide


All data and specifications are nominal values and may vary.

PUBLISHED: 4-20-2020

COLORIMETRIC SPECIFICATIONS



PRODUCT DIMENSIONS



PUBLISHED: 4-20-2020