



FEATURES



- Proprietary durable phosphor coating, for uniform solid appearance
- Multi-function PWM drivers, fully waterproof, featuring low power, high power, and turn signal modes
- Extremely bright, high-density LEDs that are visible even in direct sunlight
- Integrated mounting tabs for easy installation

GENERAL SPECIFICATIONS

Product Function	Voltage Range	Current Draw*	Wattage	CCT/ Wavelength**	Lumen Output
Low	9-16V	120 mA	1.6W	6500K	110 lm
High	9-16V	500 mA	6.6W	6500K	490 lm
Turn	9-16V	1040 mA	13.7W	6500K	1020 lm

*Current Draw @13.2v **+/-500 Tolerance

Functions: Low White, High White, and Brilliant White outputs

Driver Type: Type H High Priority Driver

Connector Type: 2 Pin JST and 4 Pin JST with T-Tap

LED Type/Count: 3014 White LED/ 192 Total

Operating Temperature: -40°C to 85°C

Length: 9" **Width:** 5.75" **Height:** 2.25"

Weight: 1lbs



What's Included:

- Two (2) LED halo rings
- Two (2) waterproof drivers
- Two (2) input wire pigtailed
- Eight (8) T-tap connectors
- Installation guide


All data and specifications are nominal values and may vary.

PUBLISHED: 4-20-2020

COLORIMETRIC SPECIFICATIONS



PRODUCT DIMENSIONS



PUBLISHED: 4-20-2020