## Stage Series 3" Pro Yellow Round LED Pod





#### **FEATURES**





- Advanced TIR optics provide high efficiency and focus
- High-intensity automotive-type LEDs
- Pin-fin heatsink design, for superior thermal dissipation
- Integrated Deutsch-style connector
- Durable powdercoated aluminum construction
- · Designed, torture tested and assembled in USA

## **GENERAL SPECIFICATIONS**

Optic	Peak Beam Intensity (Candela)	llluminance (lux @10m)	Measured Output (Lumens)	Raw Output (Lumens)	Output Color
Driving	60,900 cd	609 lux	2,700 lm	5,220 lm	Selective Yellow
Flood	2,850 cd	29 lux	2,700 lm	5,220 lm	Selective Yellow
Fog	10,900 cd	109 lux	2,700 lm	5,220 lm	Selective Yellow
Spot	118,500 cd	1,185 lux	2,700 lm	5,220 lm	Selective Yellow

**Functions:** Yellow Output **Voltage Range:** 9-16V

Current Draw (amps @ 12.8V): 2.7A

Wattage: 36W

Connector Type: Deutsch DT Connector

**Driver Type:** Integrated Driver

LED Type/Count: Cree XP-L HI/4 total

**Compliance Rating:** J575 Durability Test, SAE-F J583 **Intrusion Rating:** IP69K Waterproof, High Pressure

Operating Temperature: -40°C to 85°C

#### What's Included:

- One (1) or Two (2) Stage Series 3" LED Pods
- One (1) or Two (2) Deutsch-style wire pigtails
- One (1) or Two (2) Mounting brackets and hardware

Dimensions & Weight:

Length: 14.5" Width: 10" Height: 5" Weight: 2.5 lbs (single), 3.5 lbs (pair)

SKUs: Append "S" to the end of each SKU for single and "P" for pair

**DD6148** Stage Series 3" Pro Yellow Driving Round **DD6149** Stage Series 3" Pro Yellow Flood Round


**DD6150** Stage Series 3" Pro Yellow Fog Round **DD6151** Stage Series 3" Pro Yellow Spot Round


All data and specifications are nominal values and may vary.







## **COLORIMETRIC SPECIFICATIONS**






## **PRODUCT DIMENSIONS**







## PHOTOMETRIC SPECIFICATIONS




## **Driving Optic Perspective**




## **Driving Optic Isocandela**




**Fog Optic Isolux** 




**Fog Optic Perspective** 



Fog Optic Isocandela



# PHOTOMETRIC SPECIFICATIONS (cont.)




100.0 50.00 25.00 10.00 5.000 2.500 1.000 0.5000 0.5000 0.5000


**Flood Optic Perspective** 

185 gard of 1628 38 do 50 do 5


Flood Optic Isocandela



**Spot Optic Isolux** 



**Spot Optic Perspective** 



Spot Optic Isocandela

