

DIODE DYNAMICS

2014+ Toyota Tundra

Stealth Light Bar Kit Installation Guide



8. If you purchased the 30" light bar option, replace the lower grille. To do so, insert it top side first and then angle it into place as you snap the tabs back into place to complete the installation.

NEED MORE HELP?

Scan the QR code to link to our installation video online!

We've taken the time to test our products on your vehicle. We can guarantee compatibility and fitment the first time – no guessing game! If you need more help with installation, watch our step-by-step video to walk you through the process.

You Tube



Please contact **Diode Dynamics** should you have any questions about the installation or wiring process, at **314-205-3033** (10a-5p CST) or **contact@diodedynamics.com**.

This installation guide is for the following SKUs:

DD6058 Tundra SS30 Stealth Lightbar Kit White Driving
DD6059 Tundra SS30 Stealth Lightbar Kit White Flood
DD6060 Tundra SS30 Stealth Lightbar Kit White Combo
DD6061 Tundra SS30 Stealth Lightbar Kit Amber Driving
DD6062 Tundra SS30 Stealth Lightbar Kit Amber Flood
DD6063 Tundra SS30 Stealth Lightbar Kit Amber Combo

DD6052 Tundra SS42 Stealth Lightbar Kit White Driving
DD6053 Tundra SS42 Stealth Lightbar Kit White Flood
DD6054 Tundra SS42 Stealth Lightbar Kit White Combo
DD6055 Tundra SS42 Stealth Lightbar Kit Amber Driving
DD6056 Tundra SS42 Stealth Lightbar Kit Amber Flood
DD6057 Tundra SS42 Stealth Lightbar Kit Amber Combo

100% SATISFACTION
GUARANTEE

3 YEAR
WARRANTY



DIODE DYNAMICS

PERFORMANCE LIGHTING TECHNOLOGY

2014+ Toyota Tundra

Stealth Light Bar Kit Installation Guide



DIODE DYNAMICS

2014+ Toyota Tundra

Stealth Light Bar Kit Installation Guide

DIODE DYNAMICS

2014+ Toyota Tundra

Stealth Light Bar Kit Installation Guide

Thank you for your purchase of this custom-designed LED light bar kit for your 2014+ Toyota Tundra! This kit utilizes both factory and included hardware from the light bar to mount the bracket to the vehicle.

3 YEAR
WARRANTY

Tools Needed: 14mm socket, 14mm wrench, flat head screwdriver or plastic trim tool



WATCH THE INSTALLATION VIDEO ONLINE!

Scan the QR code on page 3



1. Remove the lower grille by gently loosening it starting from the outside, working your way to the center. Some of the tabs might be hard to loosen, so we recommend using a flathead screwdriver to help loosen them.



2. Once the tabs have been loosened, push the grille from the bottom while pulling up at the same time. It will take some maneuvering, but remove the grille from the truck and set it aside.

Note: the lower grille will not be reused if you purchased the 42" light bar option. The lower grille will be reinstalled if you purchased the 30" light bar option.



3. From underneath the truck, remove three 14mm nuts from the light bar bracket mounting points on the bumper. These nuts might be tight, so we recommend loosening them with a 14mm socket and then using a wrench to remove them completely.



4. Put the light bar brackets in place, but do not replace the original nuts yet. Simply set the brackets in place to mount the light bar to the brackets. We will secure the brackets in step 6.



5. Mount the light bar to the brackets.

Note: if you purchased the 30" light bar option, use the 10mm bolts included with the brackets themselves. If you purchased the 42" light bar option, use the low profile hex bolts that are included with the light bar in the universal mounting bracket box.

6. Tuck your wiring behind the light bar so you can wire it later on. Once the light bar is securely mounted to the brackets, mount the brackets to the bumper using the original nuts.



7. Route your wiring, test thoroughly, and aim the light bar in the desired direction before tightening all mounting hardware. Please check your local laws and regulations for aiming, installation, and applicability.

See back for further instructions.