


FESTOON LEDs



194 HP6

Bright, omnidirectional LEDs for even illumination
Diffusing lens for modern appearance
Non-polar, fully constant-current circuit

\$10.00



Available sizes:

29mm, 31mm, 36mm,
39mm, and 41mm

The Diode Difference



After over a decade in business, Diode Dynamics is the most trusted name in automotive LED lighting. Unlike other LED distributors, we engineer all our products right here in the United States, for high quality and performance. All lighting products are fully tested and measured using an integrating sphere and spectroradiometer, to provide the exact color and true total lumen output. We pride ourselves in offering only the highest quality LED products, that will exceed your expectations.

DIODE DYNAMICS

PERFORMANCE LIGHTING TECHNOLOGY



INTERIOR LED LIGHTING UPGRADES



HP6 SPECIFICATIONS

OPERATION

Advanced integrated inductive drive circuit for superior performance and reliability.

OUTPUT

Eight high-power LEDs are arranged in an omnidirectional pattern with a frosted cover to provide even light distribution.

FITMENT

Sturdy aluminum base terminal to ensure a correct and secure fitment.

RELIABILITY

Unique constant-current drive circuit ensures high reliability over time.



DIODE DYNAMICS
PERFORMANCE LIGHTING TECHNOLOGY

(314) 205-3033
contact@diodedynamics.com
www.diodedynamics.com



MINI WEDGE LEDS

DESIGNED FOR PERFORMANCE

194 HP5 COOL WHITE

TruLux™	92 lumens
Power Consumption:	1.09 watt
Typical Draw:	83 mA

194 HP5

92 lumens (3x standard bulb)
High brightness with diffusing lens
for excellent output



\$10.00



Common Applications

- ▶ Map Lights
- ▶ License Plate
- ▶ Dome Lights
- ▶ Door Lights
- ▶ Sidemarker
- ▶ Trunk Lights



3 YEAR
WARRANTY

Compatible bulb sizes:

T-10, 147, 152, 158, 159, 161, 168, 184,
192, 193, 259, 280, 285, 447, 464, 555,
558, 585, 655, 656, 657, 1250, 1251,
1252, 2450, 2652, 2921, 2825



OPTICS

Molded diffusing optic provides omnidirectional output, for high performance.

COLOR

High-power genuine Samsung 2323 LEDs, tested to provide perfect color uniformity.

OPERATION

Integrated copper plating dissipates heat quickly, allowing for high operating current and brightness.

RELIABILITY

Unique constant-current drive circuit ensures high reliability over time.

FITMENT

Sturdy, thick-gauge wrap around contact wires ensure a reliable connection in socket.




194 HP3

58 lumens (2x standard bulb)
Diffusing lens for excellent
output pattern



\$6.00



MODERN LED OUTPUT

